

应用场所 Application

- 适用于船舶、海洋平台、港口、码头等作露天场所投光、泛光照明。
- Suitable for spotlight and floodlight illumination in open spaces like ships, offshore platforms, ports and wharfs, etc..



灯体 Housing

- 不锈钢拉伸成型，表面喷塑
- Housing in stretching formed stainless steel, powder coated surface

透明罩 Transparent cover

- 钢化玻璃
- Toughened glass

卡扣 Buckle

- 不锈钢
- Stainless steel

电气 Electric

- 恒流恒压驱动电源，宽电压输入
- Constant current constant voltage drive power, wide voltage input

选配表 Selection table

型号 Type	额定电压(V) Rated voltage	额定功率(W) Rated power	光通量(lm) Luminous flux	重量(kg) Weight
CTG32-LED150	220V~240V AC 50/60Hz	150W	16200	18.0
CTG32-LED180		180W	19400	18.0
CTG32-LED200		200W	21600	18.0

技术参数 Technical parameters

执行标准 Conformity to standards	GB 11472, GB 7000.7, GB/T 24954, IEC 60598, CCS 入级规范 (CCS standard)
环境温度 Ambient temperature	-40°C~+55°C
光源类型 Light source	LED 模组 LED module
色温 Color temperature	5700K ± 250K (3000K、4000K可选 Optional)
显色指数 Color rendering index	Ra ≥ 70
防护等级 Degree of protection	IP66
电缆入口 Cable entris	2 × Φ20.5孔, 配2 × FQM-IV, M20 × 1.5格兰(黄铜镀镍), 适用于Φ5~Φ12mm电缆 2 × Φ20.5 hole, with 2 × FQM-IV, M20 × 1.5 gland (Nickel plated brass), suitable for Φ5-Φ12mm cable
接线端子 Terminal	3 × 1.5~4mm ²

外形尺寸 Outline dimension

